

ORDERING AMERICAN PANEL HEARTH PADS

FRAMES:

Original Edge: **OE**- (available in Type 1 & Type 2)
 Colonial Edge: **CE**-(available as Type 2 only)

SHAPES:

Corner (**sl-single lop**)
 Standard (**dl-double lop**)
 Extensions (**ext**)
 Square or Rectangle (**sq**)
 Octagon (**oct**)

TYPES:

Type 1 (**T1**) Ember Protection Only **R=0**
 Type 2 (**T2**) Ember and Thermal Protection **R=1.592**

Available in the following sizes:

12"x48" ext/sq
 18"x48" ext/sq
 24"x30" dl/sq/oct/ped
 24"x36" dl/sq/oct/ped
 32"x32" sl/dl/sq/oct/ped
 36"x36" sl/dl/sq/oct/ped
 40"x40" sl/dl/sq/oct/ped
 44"x44" sl/dl/sq/oct/ped
 48"x48" sl/dl/sq/oct/ped
 48"x54" dl/sq/oct/ped
 54"x48" dl/sq/oct/ped
 54"x54" sl/dl/sq/oct/ped
 60"x60" sl/dl/sq/oct/ped

Available in the following tiles/stones:

Carmel - c
 Black Jack - bj
 High Plains - hp
 Night Shadow - ns
 Delhi Sky -dsky
 Terracotta - tc
 White Sand - ws
 Tartara - tt
 Imperial Black - ib
 Volcanic Sand - vs
 Desert Storm - ds
 Safari Sand - ss
 Asian Slate - as
 Indian Silver Slate - iss
 Montana Flagstone - mf
 Copper Slate Polished - csp

ORDERING HEARTH PAD

SPECIAL OPTIONS

Inlays tile or slate
 Venetian - vil (tile or slate)
Special Cut
 Random Sq Cut - rsc (slate only)

Venetian Inlay

Random Sq Cut

Build Item Number

Step 1 Select frame & Type	OE-T1 OE-T2 CE-T2
Step 2 Select Size	OE-48-T1 OE-48-T2 CE-48-T2
Step 3 Select Shape	OE-48-dl-T1 OE-48-sl-T2 CE-48-dl-T2
Step 4 (1) Select Tiles/Stones	OE-48-dl-c-T1 OE-48-sl-c-T2 CE-48-dl-c-T2
Add Inlay (2) (Optional)	OE-48 dl c-vil-T1 OE-48 dl c-vil-T2 CE-48 sl c-vil-T2
Add Special Cut (3) (Optional)	OE-48 dl as-rsc-T1 OE-48 dl as- rsc-T2 CE-48 sl as-rsc-T2

Type 1(T1) – Ember Protection Only

- Available up to 54 x 48" only
- Powder coated frames
- Available in Original frame only (½" high x ⅜" wide)
- Tubed aluminum for maximum strength
- No overspray issues on grout, frames painted prior to tile/slate installation
- ½" non-combustable cement board
- 0-flame spread / 0-smoke development – per ASTM E84 and ASTM E136
- Excellent bonding characteristics

Type 2 (T2) – Ember & Thermal Protection (Original Edge or Colonial Edge) R-Value 1.592

- Powder coated frames
- Available in Original frame (1¼" high x ½" wide) or Colonial frame (1¼" high x ¾" wide)
- Tubed aluminum for maximum strength
- No overspray issues on grout, frames painted prior to tile/slate installation
- ½" mineral fiber board (thermal protection)
- ¼" non-combustible cement board
- 0-flame spread / 0-smoke development – per ASTM E84 and ASTM E136
- Excellent bonding characteristics
- Does not rely on air pocket for thermal value

(Examples) Final Description:

- (1)
 Original Edge - 48 DL Carmel - Standard – TYPE 1
 Original Edge - 48 DL Carmel - Standard – TYPE 2
 Colonial Edge - 48 SL Carmel - Corner – TYPE 2
- (2)
 Original Edge - 48 DL Carmel-Venetian Inlay – Standard – TYPE 1
 Original Edge - 48 DL Carmel-Venetian Inlay – Standard – TYPE 2
 Colonial Edge - 48 SL Carmel-Venetian Inlay – Corner – TYPE 2
- (3)
 Original Edge - 48 DL Asian Slate-Random Sq Cut – Standard – TYPE 1
 Original Edge - 48 DL Asian Slate-Random Sq Cut – Standard – TYPE 2
 Colonial Edge - 48 SL Asian Slate-Random Sq Cut – Corner – TYPE 2

Ordering a Pedestal 48x48 dl ped-c
 Or (48 Standard – pedestal – Carmel)
Low Profile Pedestal LP-48x48 R=2.08

Pedestals